

# GOLF CAR / UTILITY VEHICLE

## 2009 - 2010 Winter Service Special

MANUFACTURER RECOMMENDED

**Fleet Pricing Only • 20 Vehicle Minimum to Qualify**

- **GAS DS • PRECEDENT • TURF/CARRYALL VEHICLES**

Price includes wash, inspection and adjustments as per list on back of flyer, with oil change; air filter, new spark plug, oil filter and 2 fuel filters; pick up and delivery.

**\$105 per vehicle within 30 miles of a Century branch.**

**\$110 per vehicle within 30 - 60 miles of a Century branch.**

*Call for quote for over 60 miles.*

- **ELECTRIC DS • PRECEDENT • TURF/CARRYALL VEHICLES**

Price includes wash, inspection and adjustment as per list on back of flyer, and pick up and delivery.

**\$67 per vehicle within 30 miles of a Century branch.**

**\$72 per vehicle within 30 - 60 miles of a Century branch.**

*Call for quote for over 60 miles.*

*All other needed repairs will be quoted for approval by customer. All approved repairs will have labor and materials discounted by 15% from retail prices.*



**Club Car**®

**CARRYALL**



**Don't wait! Call your local Century Service Manager or Sales Representative for details!**

**CENTURY** *Equipment*

1-800-346-0066



Shop Online

[www.centuryequip.com](http://www.centuryequip.com)

# Annual Service Procedure Sheet

## ELECTRIC

- Power wash vehicle.
- Inspect front wheel bearings.
- Inspect, clean and adjust rear brakes.
- Check and fill differential oil to proper level.
- Check steering linkage and adjust as required, including gear box.
- Check front alignment. Re-align if needed.
- Lube front suspension and all other fittings.
- Lube brake shaft bearing and return spring as required.
- Check accelerator pedal and linkage for free movement and return as required.
- Lube accelerator push rod pivots.
- Check and correct battery water level.
- Check battery tops and terminals.
- Check battery hold down and coat terminal connections.
- Check charger receptacle.
- Check car for proper solenoid engagement and V-glide slide.
- Check reverse buzzer operation.
- Check motor wires and resistors for loose connections.
- Check F&R switch for free contact movement, lube if necessary.
- Check tires for wear and damage and adjust tire pressure: 18 to 20 PSI.
- Check seat bolts. Tighten if necessary.



**CENTURY** *Equipment*

## GAS

- Power wash vehicle.
- Inspect front wheel bearings.
- Inspect, clean and adjust rear brakes.
- Check and fill differential oil to proper level.
- Check transmission oil level.
- Check steering linkage and adjust as required, including gearbox.
- Check front alignment. Re-align if needed.
- Lube front suspension and all other fittings.
- Lube brake shaft bearing and return spring as required.
- Check accelerator pedal and linkage for free movement and return as required.
- Lube governor and accelerator pivots.
- Check governor settings, adjust to specs.
- Replace air filter and check mounting bolts.
- Replace fuel filters, check fuel lines and tank as required.
- Change engine oil and filter. Check oil light operation.
- Check torque converter operation.
- Check transmission shift linkage.
- Lube F & R lever pivot.
- Check exhaust for leaks or breaks.
- Check condition of muffler and brackets.
- Inspect drive belt.
- Inspect starter/generator brushes.
- Check starter/generator belt, adjust as required.
- Check tires for wear and damage and adjust tire pressure: 12 to 14 PSI.
- Check seat bolts, engine mounts, differential, F & R lever screw. Tighten if necessary.
- Inspect battery cables. Spray cables. Check water level & hold downs.
- Check reverse buzzer operation.
- Check charging system.